



IndiTech

Values 'n' Valves



PRODUCT RANGE

“We don't just **sell products**; we provide **complete solutions** to your fluid control problems”

SCAN ME



WS QR CODE



CONTROL VALVE

Size	NPS 0.5 to NPS 24 (DN15 to DN600)
Pressure Rating	CL150 to CL2500
Design Standard	ASME B16.34; ISA 75.01.01
Body Material	A216 WCB; A217 WC6 / WC9; A351 CF8M
End Connections	Flanged / Socket Weld / Butt Weld
Leakage Class	Class IV / Class V / Class VI
Operation	Pneumatic / Motorized / Manual

3 - WAY GLOBE VALVE

Size	NPS 1 to NPS 24 (DN25 to DN600)
Pressure Rating	CL150 to CL2500
Design Standard	ASME B16.34; ISA 75.01.01
Body Material	A216 WCB; A217 WC6 / WC9; A351 CF8M
End Connections	Flanged / Socket Weld / Butt Weld
Leakage Class	Class IV / Class V
Operation	Pneumatic / Motorized / Manual
Duty	Control / On-Off
Types	Diverting / Mixing



BLOWDOWN VALVE (CBD/IBD)

Size	NPS 1 to NPS 3 (DN25 to DN80)
Pressure Rating	CL300 to CL2500
Body Material	A105; A182 F11 / F22 / F91 / F316
End Connections	Flanged / Socket Weld / Butt Weld
Leakage Class	Class IV / Class V
Operation	Motorized / Lever Operated / Manual

DESUPERHEATER / ATTEMPERATOR

Steam Line Size	NPS 1 to NPS 80 (DN25 to DN2000)
Pressure Rating	CL150 to CL2500
Body Material	A105; A106 Gr. B; A182 F11 / F22; A335 P11 / P22
Nozzle Material	SS 316 / SS 410 (Stellited Optional)
Type	Separate Control Valve / In-built Control Valve
Turndown	4:1 to 40:1



PRDS STATION / PRESSURE REDUCING STATION

Inlet x Outlet Pipe Size	NPS 1 to NPS 24 x NPS 1 and above
Pressure Rating	CL150 to CL2500
Piping Material	A106 Gr. B; A335 P11 P22 / P91
End Connections	Flanged / Socket Weld / Butt Weld
Configuration	Separate CV & DSH / Combined PRDS



TURBINE BYPASS VALVE / COMBINED PRDS VALVE

Inlet x Outlet Size	NPS 1 to NPS 24 x NPS 1 and above
Pressure Rating	CL150 to CL2500
Body Material	A216 WCB; A217 WC6 / WC9; A105; A182 F11 / F22
End Connections	Flanged / Socket Weld / Butt Weld
Leakage Class	Class IV / Class V
Operation	Pneumatic / Motorized / Electro-Hydraulic
Body Configurations	Globe / Angle



QUICK CLOSING NON-RETURN VALVE (QCNRV)

Size	NPS 4 to NPS 24 (DN100 to DN600)
Pressure Rating	CL150 to CL600
Service Media	Steam / Water / Gas
End Connections	Flanged / Butt Weld
Body Material	A216 WCB; A217 WC6 / WC9; A351 CF8M
Operation	Pneumatic

Our Global Presence



Argentina | Bangladesh | China | Chile | Ethiopia | Egypt | Honduras | Iran | Indonesia | Kenya
 Malaysia | Mexico | Nigeria | Philippines | Portugal | Poland | Russia | Sri Lanka | Saudi Arabia South
 Africa | South Korea | Turkey | Thailand | Tunisia | UAE | UK | USA | Vietnam

We are Trusted By



HEAD OFFICE

FACTORY

**INNOVATION
CENTRE**

21, Shubham, Prosperity Society, Karve Nagar, Pune - 411052
 Tel: +91 20 25420021, 9518330514, 7066040407, 7030530022
 Email: info@inditechvalves.com

Plot No. 5, Gate No. 171, 172 & 177, Village Dhanore, Alandi-Markal
 Road, Pune - 412105, India

Plot No. D102, KSSIDC Industrial Estate, Gamanagatti,
 Hubli - 580026, India